


# DIN 7500 M, Thread forming screw, M 6x12, ST, zinc-plated, standard, 5 µm, Zn5/An/T0, Z 3



<b>Article number</b> 2075007612	<b>Weight in kg</b> 0.001
<b>Customs number</b> 73181499	<b>Material</b> Steel
<b>Quality</b> ST	<b>Coating</b> zinc-plated, standard, 5 µm, Zn5/An/T0
<b>Force application type</b> Pozidriv cross recess	<b>Diameter</b> 6 mm
<b>Length</b> 12 mm	

## Product details

form M - countersunk head acc. DIN 965.

Material	Steel
Force application type	Pozidriv cross recess
Length	12 mm
Total length l	12 mm
Norm	DIN 7500 M
Diameter	6 mm
Quality	ST
Force application	Z 3
Height of the head k	3 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	11 mm

Diameter d 6 mm

### Product variants

Diameter (mm)	2,5	3	4	5	6	8
Length (mm)						
6		•	•			
8		•	•	•		
10	•	•	•	•		
12		•	•	•	•	
16		•	•	•	•	
20		•	•	•	•	
25			•	•	•	•
30			•		•	•
35			•			•
40				•	•	