


DIN 7982 C, countersunk head tapping screw, ST 4, 2x19, ST, zinc-plated, standard, 5 µm, Zn5/An/T0, Z 2



Article number
20798294219

EAN
None

Weight in kg
0.001

Customs number
73181491

Material
Steel

Quality
ST

Coating
zinc-plated, standard, 5 µm, Zn5/An/T0

Force application type
Pozidriv cross recess

Diameter
4,2 mm

Length
19 mm

Product details

C form with cone end.

Material	Steel
Force application type	Pozidriv cross recess
Length	19 mm
Total length l	19 mm
Norm	DIN 7982 C
Diameter	4.2 mm
Quality	ST
Force application	Z 2
Height of the head k	2.5 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	8.1 mm

Diameter d 4.2 mm

Remarks

Standard was withdrawn. DIN corresponds to ISO 7050. Changed head dimensions for ISO. Item is delivered according to DIN.

Product variants

Diameter (mm)	2,2	2,9	3,5	3,9	4,2	4,8	5,5	6,3
Length (mm)								
6,5	•	•						
8			•					
9,5	•	•	•	•	•	•		
13	•	•	•	•	•	•	•	
16	•	•	•	•		•	•	•
19		•	•	•	•	•	•	•
22				•	•	•		
25		•		•	•	•	•	•
32		•	•	•		•	•	•
38			•	•	•	•	•	•
45			•	•	•	•	•	•
50			•		•	•	•	•
60					•	•	•	•
70					•	•	•	•
80					•	•	•	•
90						•	•	
100						•	•	