

DIN 705 A, Adjusting ring, 30 mm, SpSt, zinc-plated, standard, 5 μ m, Zn5/An/T0



Article number
23070530

EAN
None

Weight in kg
0.111

Customs number
73269098

Material
Spring steel

Quality
SpSt

Coating
zinc-plated, standard, 5 μ m, Zn5/An/T0

Inner diameter
30 mm



Product details

A form, fastening using threaded pin DIN 914/ISO 4027.

Width b	16 mm
Material	Spring steel
Inner diameter	30 mm
Norm	DIN 705 A
Quality	SpSt
Inner diameter di	30 mm
Outer diameter da	45 mm
Coating	zinc-plated, standard, 5 μ m, Zn5/An/T0
Diameter d	8 mm

Remarks

up to d1 = 70 mm with 1 threaded pin,

from d1 = 80 mm with 2 threaded pins

Standard was withdrawn without a replacement. Similar to DIN 705. Attention: Possibility of hydrogen embrittlement acc. ISO 4042. For further questions, please contact us under: engineering@keller-kalmbach.com

Product variants

Coating	burn.	pin	zinc-plated, standard, 5 µm, Zn5/An/T0
Inner diameter (mm)			
4		•	
5		•	•
6		•	•
8		•	•
10		•	•
12		•	•
14		•	
15		•	•
16		•	•
18		•	•
20	•	•	•
22		•	•
24		•	•
25		•	•
28		•	•
30		•	•
32		•	
35		•	•
36		•	
40		•	•
45		•	•
50		•	•
55		•	
60	•	•	•
70		•	
80		•	•
85		•	
90		•	
100		•	•
110			•
120		•	