

DIN 933, hexagon head bolt, M 24x340, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0



|                               |                                                   |
|-------------------------------|---------------------------------------------------|
| Article number<br>24093324340 | Weight in kg<br>1.123                             |
| Customs number<br>73181588    | Material<br>Steel                                 |
| Quality<br>8.8                | Coating<br>zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Diameter<br>24 mm             | Length<br>340 mm                                  |
| Force application<br>SW 36    | Norm<br>ISO 4017 / DIN 933                        |



Product details

Threaded close up to the head.

|                        |                    |
|------------------------|--------------------|
| Material               | Steel              |
| Force application type | External hex       |
| Length                 | 340 mm             |
| Norm                   | ISO 4017 / DIN 933 |
| Total lenght l         | 340 mm             |
| Norm                   | ISO 4017           |
| Diameter               | 24 mm              |
| Quality                | 8.8                |
| Height of the head k   | 15 mm              |
| Force application      | SW 36              |

|            |                                        |
|------------|----------------------------------------|
| Coating    | zinc-plated, standard, 5 µm, Zn5/An/T0 |
| Diameter d | 24 mm                                  |

Remarks

Standard was withdrawn. DIN similar to ISO 4017. Changed SW for ISO.Sizes M 10, M 12, M 14 and M 22 only available in DIN 933. For further sizes see ISO 4017.

Application

Universell einsetzbar, vor allem im Maschinenbereich

Product variants

| Force application  | SW 36 |
|--------------------|-------|
| Norm               |       |
| ISO 4017 / DIN 933 | .     |