


# ISO 14579, Cap screw with hexalobular socket, M 6x20, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0, TX 30



**Article number**  
2414579620

**Weight in kg**  
0.007

**Customs number**  
73181595

**Material**  
Steel

**Quality**  
8.8

**Coating**  
zinc-plated, standard, 5 µm, Zn5/An/T0

**Force application type**  
Hexalobular internal

**Diameter**  
6 mm

**Length**  
20 mm

## Product details

Material	Steel
Total length l	20 mm
Length	20 mm
Norm	ISO 14579
Diameter	6 mm
Height of the head k	6 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	10 mm
Thread length b	20 mm
Force application type	Hexalobular internal
Quality	8.8
Force application	TX 30

Diameter d

6 mm

## Properties

Optimale Kraftübertragung bei Verbindungselementen mit Innensechsrundantrieb (TX), durch großflächigen Kraftangriff über die Flanken des Antriebs und nicht punktuell.

## Application

Vielfältige Anwendungsberieche, zum Beispiel für im Maschinenbau, der Möbelindustrie sowie im Sanitär,- und Heizungsbau.

## Product variants

Diameter (mm)	3	4	5	6	8	10	12	16
Length (mm)								
8	•	•		•				
10		•		•				
12		•	•	•	•			
14					•			
16		•	•	•	•	•		
20	•	•	•	•	•	•		
25	•	•	•	•	•	•	•	
30		•	•	•	•	•	•	
35			•	•	•	•	•	
40			•	•	•	•	•	
45				•	•			
50				•	•	•		•
60				•		•		
65							•	
70						•		
75				•	•			
80				•	•			
90				•				
110					•			
200				•				