

DIN 913, Set screw with flat point, M 8x35, 45 H, zinc-plated, standard, 5 µm, Zn5/An/T0



Article number 270913835	Weight in kg 0.01
Customs number 73181548	Material Steel
Quality 45 H	Coating zinc-plated, standard, 5 µm, Zn5/An/T0
Force application type Hex socket	Diameter 8 mm
Length 35 mm	

Product details

With internal hexagon and rounded taper.

Material	Steel
Depth t	5 mm
Force application type	Hex socket
Length	35 mm
Total length l	35 mm
Diameter d1	5.5 mm
Norm	ISO 4026
Diameter	8 mm
Quality	45 H
Force application	ISK 4
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0

Diameter d

8 mm

Remarks

Standard was withdrawn. DIN similar to ISO 4026. Attention: Possibility of hydrogen embrittlement acc. ISO 4042. For further questions, please contact us under: engineering@keller-kalmbach.com

Product variants

Diameter (mm)	2	2,5	3	4	5	6	8	10	12	14	16	20	24	30
Length (mm)														
3	•		•											
4	•		•	•	•									
5	•	•	•	•	•	•								
6	•		•	•	•	•	•							
8			•	•	•	•	•	•						
10	•		•	•	•	•	•	•	•					
12			•	•	•	•	•	•	•					
14			•		•	•	•	•						
16			•	•	•	•	•	•	•					
18						•						•		
20			•	•	•	•	•	•	•		•			
25			•	•	•	•	•	•	•		•			
30				•	•	•	•	•	•		•			
35				•	•	•	•	•	•		•	•		
40				•	•	•	•	•	•		•	•		
45					•	•	•	•	•		•			
50					•	•	•	•	•		•			
55							•	•						
60						•	•	•	•		•	•		
70						•	•	•	•		•			
80							•	•	•		•	•		
90							•	•	•		•			
100							•	•	•	•	•	•		
110							•							
120									•			•	•	
150												•		
200														•