

# ISO 15977 FAKKT blind rivet, dome head, 3x8, AL/ST, CR: 3,5-5



**Article number**  
580000110330080

**EAN**  
None

**Weight in kg**  
0.001

**Customs number**  
83082000

**Quality**  
AL/ST

**Coating**  
pln

**Clamping range min.**  
3,5 mm

**Clamping range max.**  
5 mm

**Diameter**  
3 mm

**Length**  
8 mm

## Product details

Material	Aluminium
Length	8 mm
Length of rivet mandrel p	26 mm
Norm	ISO 15977
Tensile force	800 N
Diameter	3 mm
Bore hole diameter	3,1 mm
Height of the head k	1 mm
Coating	pln
Diameter of the head dk	6.3 mm
Head type	dome head
Clamping range max.	5 mm
Clamping range min.	3.5 mm

Shear force	500 N
Diameter of rivet mandrel dm	1.7 mm
Material mandrel	Steel
Quality	AL/ST
Length of rivet sleeve l	8 mm
Material sleeve	Aluminium
Diameter d	3 mm

## Remarks

Standard DIN 7337 A was withdrawn. DIN similar to DIN EN ISO 15977.

## Product variants

Diameter (mm)	3	3,2
Length (mm)	•	•
8		