# ISO 15983 FAKKT blind rivet, dome head, 4,8x35, A2/A2, CR: 25-30





**Article number**
580000120048350

**Weight in kg**
0

**Customs number**
83082000

**Quality**
A2/A2

**Clamping range min.**
25 mm

**Clamping range max.**
30 mm

**Diameter**
4,8 mm

**Length**
35 mm

## Product details

| | |
|---|---|
| Material | Stainless steel |
| Length | 35 mm |
| Lenght of rivet mandrel p | 27 mm |
| Norm | ISO 15983 |
| Tensile force | 5340 N |
| Diameter | 4.8 mm |
| Bore hole diameter | 4,9 mm |
| Height of the head k | 1.1 mm |
| Coating | pln |
| Diameter of the head dk | 9.5 mm |
| Head type | dome head |
| Clamping range max. | 30 mm |
| Clamping range min. | 25 mm |
| Shear force | 4230 N |



Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de

| | |
|---|---|
| Diameter of rivet mandrel dm | 2.9 mm |
| Material mandrel | A2 stainless steel |
| Quality | A2/A2 |
| Lenght of rivet sleeve l | 35 mm |
| Material sleeve | A2 stainless steel |
| Diameter d | 4,8 mm |

## Remarks

Standard DIN 7337 A was withdrawn. DIN similar to DIN EN ISO 15983.

## Product variants

| Diameter (mm) | 4,8 |
|---|---|
| **Length (mm)** | |
| 35 | • |



Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de