FAKKT blind rivet, dome head, 6x16-ML: 35 mm, ST/ST, zinc-plated, standard, 5 µm, Zn5/An/T0, KB: 6-10



Article number
5800001641996

Weight in kg
0

Customs number
83082000

Material
Steel

Quality
ST/ST

Coating
zinc-plated, standard, 5 µm, Zn5/An/T0

Clamping range min.
6 mm

Clamping range max.
10 mm

Length
16 mm

Product details

Material	Steel
Length	16 mm
Lenght of rivet mandrel p	35 mm
Tensile force	4800 N
Diameter	6 mm
Bore hole diameter	6,1
Height of the head k	1.9 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	12 mm
Head type	dome head
Clamping range max.	10 mm
Clamping range min.	6 mm

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de

Shear force	4300 N
Diameter of rivet mandrel dm	3.65 mm
Material mandrel	Steel
Quality	ST/ST
Lenght of rivet sleeve l	16 mm
Material sleeve	Steel
Diameter d	6 mm

Remarks

mit längerem Nietdorn von 35 mm

Product variants

Clamping range max. (mm)	10
Length (mm)	
16	•

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de