

MKT B 16-30-48/150 vz



Article number
620611630

EAN
4043315005014

Weight in kg
0.247

Customs number
73181595

Typ
B vz

Material
Stahl galvanisch verzinkt

Güte
ST

Coating
vz

Bohrerenndurchmesser d0
16 mm

Nutzlänge tfix max./min. Last
30 / 48 mm

Product details

Typ	B vz
Güte	ST
Kraftangriff	SW 24
Dübellänge	150 mm
Nutzlänge tfix max./min. Last	30 / 48 mm
Material	Stahl galvanisch verzinkt
Gewinde (d x L)	M 16 x 90 mm
Bohrerenndurchmesser d0	16 mm
Coating	vz

Technical approval

European Technical Approval, Option 7, non-cracked concrete, approval no. ETA-01/0013 M 6 to M 20.

Properties

The MKT B bolt anchors can be installed in push-through procedure. The small bore diameter ensures time-saving installation. The long cut thread makes additional application possibilities possible, such as stand-off installation or longer clamping ranges.

Assembly instruction

Installation only permitted with torque wrench.

Benefits

- small bore diameter
- time-saving, economical installation
- different anchoring depths possible and therefore also applications at very low component thicknesses.

Application

The MKT B bolt anchors are used to fasten medium-weight to heavy objects in concrete. Main areas of application include metal structures, wooden construction, substructures of wall paneling, machines, devices, and much more.

Product variants

Bohrerennendurchmesser d0 (mm)	6	8	10	12	16	20
Nutzlänge tfix max./min. Last						
10 / - mm			•			•
10 / 16 mm			•			
10 / 18 mm		•				
10 / 20 mm	•					
10 / 25 mm				•		
10 / 28 mm					•	
105 / 142 mm						•
108 / 146 mm			•			
110 / 160 mm				•		
125 / 175 mm				•		
127 / 183 mm					•	
13 / - mm				•	•	
13 / 51 mm			•			
15 / 21 mm			•			
15 / 24 mm		•				
15 / 25 mm	•					
15 / 30 mm				•		
15 / 65 mm				•		
155 / 205 mm				•		
162 / 218 mm					•	
18 / 56 mm			•			
19 / 54 mm		•				
195 / 245 mm				•		
20 / 26 mm			•			
20 / 29 mm		•				
20 / 35 mm				•		
20 / 50 mm	•					
20 / 57 mm						•

Bohrerenddurchmesser d0 (mm)	6	8	10	12	16	20
Nutzlänge tfix max./min. Last						
22 / 78 mm					•	
225 / 275 mm				•		
25 / 34 mm		•				
29 / 64 mm		•				
30 / 36 mm			•			
30 / 45 mm				•		
30 / 48 mm					•	
30 / 80 mm				•		
38 / 76 mm			•			
4 / - mm		•				
4 / 39 mm		•				
42 / 98 mm					•	
45 / 82 mm						•
5 / - mm	•	•		•	•	
5 / 27 mm						•
5 / 35 mm	•					
5 / 42 mm						•
50 / 100 mm				•		
62 / 118 mm					•	
68 / 106 mm			•			
70 / 120 mm				•		
74 / 109 mm		•				
80 / 117 mm						•
9 / 44 mm		•				
90 / 140 mm				•		
92 / 148 mm					•	