# Kunkel Brandschutzdübel KMU LF8



**Article number**
6240521

**Weight in kg**
0

**Customs number**
73181900

**Typ**
KMU-LF 8

**Material**
Stahl galvanisch verzinkt

**Oberfläche**
verzinkt

**Coating**
vz

**Bohrernenndurchmesser**
6

**Bohrlochtiefe**
42 mm

## Product details

| | |
|---|---|
| Typ | KMU-LF 8 |
| Durchmesser | 8 mm |
| Oberfläche | verzinkt |
| passend zu | SDS 2 |
| Bohrlochtiefe | 42 mm |
| Bohrernenndurchmesser | 6 |
| Material | Stahl galvanisch verzinkt |
| Coating | vz |

## Technical approval

European Technical Approval, for (redundant) multi-fasteners in cracked concrete, approval no. ETA-04/0026, galvanically zinc-plated steel.

## Properties



Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de

Simple, very speedy installation by driving in with a hammer. No screwing required when setting the dowels. Small bore diameter and low anchoring depths reduce installation times.

## Benefits

- only 6 mm hole Ø despite thread size M 8.

### Remarks

For these types of dowels, observing the exact borehole depth is extremely important. Use the SDS 2 drill bit stipulated by the approval.

### Application

The Kunkel KMU fire safety dowels are used to fasten ceiling systems, ventilation ducts, pipes and much more with screws or threaded rods.

### Product variants

| Bohrernenndurchmesser | 6 |
|---|---|
| **Bohrlochtiefe** | |
| 42 mm | • |



Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de