fischer Nylondübel SX 10x80 (25)




Article number
6265010

Weight in kg
0

Customs number
39269097

Bohrernenndurchmesser d0
10 mm

Dübellänge
80 mm



Product details

Der fischer Spreizdübel SX leitet durch die 4-fach-Spreizung die Kraft optimal in den Baustoff ein. Neben der typischen Spreizung garantiert das für die Herstellung verwendete hochwertige Nylon die sichere und dauerhafte Befestigung. Der Dübel wird in Größen von 4 x 20 bis 16 x 80 mm und wahlweise mit Schraube angeboten. Der fischer Spreizdübel SX ist die erste Wahl bei der Befestigung beispielsweise von Leuchten, Leisten, Bad- und WC-Einrichtungen sowie leichten Wandschränken in Beton und Porenbeton, aber auch im Mauerwerk aus Voll- oder Lochbaustoffen. Die Varianten mit angeformtem Rand verhindern, dass der Dübel ins Bohrloch rutscht. Ideal für Befestigungen in Lochbaustoffen, in Porenbeton und zur Putzüberdeckung sind die Varianten mit größerer Verankerungstiefe.

Typ	SX
Ausführung	ohne Schraube
Dübellänge	80 mm
Passend zu Schraubendurchmesser	6,0 - 8,0 mm
Min. Bohrlochtiefe	95 mm
Min. Plattendicke dp	-
Bohrernenndurchmesser d0	10 mm

Properties

Made of nylon, weather-resistant and halogen-free. Has universal applications in conjunction with wood or chipboard screws. Powerful 4x expansion for the highest holding values. Distinct dowel edge prevents it from slipping deeper. Integrated knock-in stop makes push-through installation possible. Stable anti-rotation lock. With long expansion zone for larger anchoring depths in perforated bricks, aerated concrete and for spanning plaster.

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de

Benefits

- powerful 4x expansion

- integrated knock-in stop

- dowel edge prevents it from slipping deeper.

Remarks

The required screw length results from dowel length + non-structural materials, such as plaster + thickness of the fixture + 1 x screw diameter.

Application

The Fischer SX nylon dowels are used to fasten light objects in concrete, aerated concrete, masonry, sand-lime bricks, solid plasterboard or perforated bricks. Main application areas include building blocks with porous microstructures and low compressive strength and perforated brick or sand-lime brick.

Product variants

Bohrernenndurchmesser d0 (mm)	10
Dübellänge (mm)	
80	•

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de