

ISO 14579, Cap screw with hexalobular socket, M 10x30, 8.8, Zinc-nickel, black, 8 μm, ZnNi8/Fn/T2 μ0,09 - 0,14, MK, TX 50



Article number
I14579AHCSEW1030

EAN
None

Weight in kg
0.028

Customs number
73181568

Material
Steel

Quality
8.8

Coating
Zinc-nickel, black, 8 μm,
ZnNi8/Fn/T2 μ0,09 - 0,14

Force application type
Hexalobular internal

Diameter
10 mm

Length
30 mm

Product details

Material	Steel
Total length l	30 mm
Length	30 mm
Norm	ISO 14579
Diameter	10 mm
Height of the head k	10 mm
Coating	Zinc-nickel, black, 8 μm, ZnNi8/Fn/T2 μ0,09 - 0,14
Diameter of the head dk	16 mm
Thread length b	30 mm
Force application type	Hexalobular internal
Quality	8.8

Force application	TX 50
Diameter d	10 mm

Properties

Optimale Kraftübertragung bei Verbindungselementen mit Innensechsrundantrieb (TX), durch großflächigen Kraftangriff über die Flanken des Antriebs und nicht punktuell.

Application

Vielfältige Anwendungsberieche, zum Beispiel für im Maschinenbau, der Möbelindustrie sowie im Sanitär,- und Heizungsbau.

Product variants

Diameter (mm)	4	5	6	8	10	12
Length (mm)						
10			•	•		
12	•	•	•			
16			•	•		
18			•			
20			•	•	•	
25			•	•	•	•
30			•		•	
35				•	•	
40			•	•	•	
45			•	•	•	
50			•	•	•	
60			•			
65				•		
70					•	
75					•	
80				•		
90			•	•	•	
100				•		