
ISO 14582, Countersunk screw with hexalobular socket, M 6x20, 8.8, zinc-plated, standard, 5 µm, Zn5/An/T0, TX 30





Article number
I14582AHAC620

Weight in kg
0

Customs number
73181558

Quality
8.8

Coating
zinc-plated, standard, 5 µm, Zn5/An/T0

Diameter
6 mm

Length
20 mm

Product details

Mit Innensechsrund und hoher Kopf

Material	Steel
Total lenght l	20 mm
Length	20 mm
Norm	ISO 14582
Diameter	6 mm
Height of the head k	3.5 mm
Coating	zinc-plated, standard, 5 µm, Zn5/An/T0
Diameter of the head dk	14.44 mm
Force application type	Hexalobular internal
Quality	8.8
Force application	TX 30

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de

Diameter d	6 mm

Product variants

Diameter (mm)	6
Length (mm)	
20	•

Keller & Kalmbach GmbH & Co. KG • Siemensstraße 19 • 85716 Unterschleißheim • + 49 (0) 89 / 83 95 0 • info@keller-kalmbach.com www.keller-kalmbach.de